

### Starline Series

	ST 2.0 T	ST 5.2 MW	ST 6.5 MW	ST-520	ST-650
Description	20 mm (3/4") Dome Tweeter	130 mm (5 1/4") Midwoofer	160 mm (6 1/2") Midwoofer	130 mm (5 1/4") 2-way component set	160 mm (6 1/2") 2-way component set
Impedance	4 Ohm	4 Ohm	4 Ohm	4 Ohm	4 Ohm
Nominal/Music Power	60/80 W	80/100 W	90/110 W	80/100 W	90/110 W
Frequency Response	5000 - 25000 Hz	65 - 7000 Hz	60-6500 Hz	60-25000 Hz	55-25000 Hz
Sensitivity	88 dB	87 dB	89 dB	87 dB	89 dB
Cone Material	Silk	Paper	Paper	Paper	Paper
Fs	1800 Hz	78 Hz	64 Hz		
Vas		4.5 ltr.	13 ltr.		
Qts		0.60	0.70		
Mounting Depth		62 mm	66 mm		
Outside Diameter		149/129 mm	166 mm		
Mounting Diameter		135 mm	156 mm		

### Powerline Series

	PO 2.5 T	PO 5.2 MW	PO 6.5 MW	PO-520	PO-650
Description	25 mm (1") Dome Tweeter	130 mm (5 1/4") Midwoofer	160 mm (6 1/2") Midwoofer	130 mm (5 1/4") 2-way component set	160 mm (6 1/2") 2-way component set
Impedance	4 Ohm	4 Ohm	4 Ohm	4 Ohm	4 Ohm
Nominal/Music Power	80/100 W	90/110 W	100/120 W	90/110 W	100/120 W
Frequency Response	4500 - 25000 Hz	65 - 7000 Hz	60 - 6500 Hz	60 - 25000 Hz	55 - 25000 Hz
Sensitivity	88 dB	87 dB	89 dB	87 dB	89 dB
Cone Material	Silk	Paper	Paper	Paper	Paper
Fs	1450 Hz	67 Hz	60 Hz		
Vas		5.4 ltr.	11 ltr.		
Qts		0.50	0.50		
Mounting Depth		62 mm	67 mm		
Outside Diameter		149/129 mm	166 mm		
Mounting Diameter		135 mm	156 mm		

### Spaceline Series

	SP 2.5 T	SP 5.2 MW	SP 6.5 MW	SP-520	SP-650
Description	25 mm (1") Dome Tweeter	130 mm (5 1/4") Midwoofer	160 mm (6 1/2") Midwoofer	130 mm (5 1/4") 2-way component set	160 mm (6 1/2") 2-way component set
Impedance	4 Ohm	4 Ohm	4 Ohm	4 Ohm	4 Ohm
Nominal/Music Power	80/100 W	90/110 W	100/120 W	90/110 W	100/120 W
Frequency Response	4500 - 30000 Hz	55 - 7000 Hz	50 - 6500 Hz	55 - 30000 Hz	50 - 30000 Hz
Sensitivity	88 dB	86 dB	87 dB	86 dB	87 dB
Cone Material	Aluminium	Aluminium	Aluminium	Aluminium	Aluminium
Fs	1600 Hz	62 Hz	60 Hz		
Vas		6.6 ltr.	11 ltr.		
Qts		0.40	0.50		
Mounting Depth		62 mm	65 mm		
Outside Diameter		149/129 mm	166 mm		
Mounting Diameter		135 mm	156 mm		

### Master 2000 Series

	Master 2000 T	Master 2000 MW	Master 2000		
Description	25 mm (1") Dome Tweeter	160 mm (6 1/2") Midwoofer	160 mm (6 1/2") 2-way component set		
Impedance	4 Ohm	4 Ohm	4 Ohm		
Nominal/Music Power	100/150 W	100/180 W	100/180 W		
Frequency Response	2500 - 25000 Hz	45 - 6000 Hz	45 - 25000 Hz		
Sensitivity	90 dB	90 dB	90 dB		
Cone Material	Silk	Aluminium	Aluminium		
Fs	710 Hz	50 Hz			
Vas		15 ltr.			
Qts		0.50			
Mounting Depth		67 mm			
Outside Diameter		166 mm			
Mounting Diameter		156 mm			

### Subwoofer

	SB-10 P-Mk2	SB-12 P-Mk2	SB-10 A-Mk2	SB-12 A-Mk2
Description	10" Subwoofer	12" Subwoofer	10" Subwoofer	12" Subwoofer
Impedance	2x 4 Ohm	2x 4 Ohm	2x 4 Ohm	2x 4 Ohm
Nominal/Music Power	250/450 W	350/600 W	250/450 W	350/600 W
Frequency Response	20 - 200 Hz	20 - 200 Hz	20 - 200 Hz	20 - 200 Hz
Sensitivity	88 dB	89 dB	88 dB	89 dB
Cone Material	Paper	Paper	Aluminium	Aluminium
Fs	37 Hz	30 Hz	34 Hz	27 Hz
Vas	25 ltr.	78 ltr.	27 ltr.	62 ltr.
Qts	0.42	0.36	0.38	0.36
Mounting Depth	140 mm	151 mm	140 mm	151 mm
Outside Diameter	259 mm	312 mm	259 mm	312 mm
Mounting Diameter	234 mm	284 mm	234 mm	284 mm

Subject to change without notice