

Bernbrunner Str. 54
74831 Gundelsheim-Höchstberg
Germany

TEL: +49 (0)7136/9509-0
FAX: +49 (0)7136/9509-30
info@ehmann-partner.de



Lautsprecherdatenblatt / Speaker Specifications

Bezeichnung / Denomination: Nova 3000 SW 250 A

Artikel-Nr. / Article-No.: 970 0080 00

Kunde / Customer: Dego

Bemerkung / Note:



Gleichstromwiderstand / DC resistance	R_{dc}	2x1.8 Ω
Nennimpedanz / Nominal impedance	Z_N	2x2 Ω
Resonanzfrequenz Resonance frequency	f_s	31.4 Hz

Spulendurchmesser
Voice coil diameter 65 mm

Spulenbreite /
Voice coil height 33 mm

Mechanische Güte /
Mechanical Q factor Q_{ms} 9.51

Elektrische Güte /
Electrical Q factor Q_{es} 0.51

Gesamtgüte
Total Q factor Q_{ts} 0.48

Dynamisch bewegte Masse /
Moving mass m_d 158.6 g

Effektive Membranfläche /
Effective piston area S_m 352 cm²

Mechanischer Widerstand /
Mechanical resistance R_{ms} 3.29 Kg/s

Nachgiebigkeit /
Compliance C_{ms} 0.16 mm/N

Antriebsfaktor /
Force factor BL 15.9 Tm


Äquivalentvolumen /
Equivalent air volume V_{as} 28.2 dm³

Wirkungsgrad /
Efficiency η 0.17 %


SPL 1W/1m 84.2 dB

SPL 2,83V/1m 87.1 dB


Frequenzgang / Frequency response [1W/1m]



Impedanzverlauf / Impedance



Klirrfaktoren / Harmonic Distortion [1w / 1m]



rot / red: K2

grün / green: K3